

MATERIAL SAFETY DATA SHEET

Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

IDENTITY: Color Release (All colors)

N.F.P.A & H.M.I.S Rating

HAZARD INDEX	HAZARD CLASS	
4 = Severe	Flammability	
3 = Serious	0	
2 = Moderate	Health	Reactivity
1 = Slight	0	0
0 = Minimal	Special Note	
	0	

SECTION I – MANUFACTURER

NAME: Stampcrete International, Ltd. 325 Commerce Blvd. Liverpool, NY 13088	Emergency Contact 800-424-9300 Information Contact 708-298-3200
---	--

SECTION II – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS:

	OSHA PE	ACGIH TLV	OTHER LIMITS	PERCENT
Calcium Carbonate				
CAS # 1317-65-3	10mg/m3	10mg/m3	N/A	83-93
Iron Oxide	10mg/m3	10mg/m3	N/A	5-15
Steric Acid	10mg/m3	10mg/m3	N/A	2

None of the remaining components of the mixture are considered Hazardous Material or carcinogens (1910.1200 Hazard Communication (d)(4)).

TRANSPORTATION INFORMATION:

DOT Classification: Not Regulated
Labeling Requirements: None Per 172-400(b) table
Marking Requirements: Proper shipping name and identification number
Placecard Requirement: None Required
Emergency Response Guide: Not applicable

National Motor Freight: (NMF-100-0): Calcium Carbonate, N.O.I. Bags, Boxes, Barrels, Pails, Item 43770. Class LTL=50 TL=35.

SECTION III – PHYSICAL CHEMICAL CHARACTERISTICS

Boiling Point: NA	Specific Gravity (H2O = 1): NA
Vapor Pressure (mm Hg): NA	Melting Point: NA
Vapor Density (Air = 1): NA	Evaporation (Ether=1): NA
Appearance: Dry powder, Color varies.	

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flash Point (Tag Closed Cup): NA
Flammable Limits: LFL: NA UEL: NA
Extinguishing Media: NA
Special Fire Fighting Procedures: NA
Unusual Fire and Explosion Hazards: None