

MATERIAL SAFETY DATA SHEET
Complies with OSHA Hazard Communication Standard, 29 CFR 1910.1200

IDENTITY

Liquid Release

Product Name: Odorless Minerals Spirits
Chemical Name: Combustible Liquid N.O.S. (Stoddard Solvent) NA 1993 PG 111
Product Appearance: Clear Liquid
Material Use: Paint Thinner, Solvent Carrier for Petroleum Based Products

N.F.P.A. & H.M.I.S. RATING

HAZARD INDEX	HAZARD CLASS	
4 = Severe	Flammability	
3 = Serious	2	
2 = Moderate	Health	Reactivity
1 = Slight	1	0
0 = Minimal	Special Note	
	0	

SECTION 1 – MANUFACTURER

Stampcrete International, Ltd. 325 Commerce Drive Liverpool, NY 13088	Emergency Contact (24 hours) 800-424-9300 General Information Contact (8am-5pm M-F) 800-233-3298
---	---

SECTION 2 – HAZARDS INGREDIENTS

	CAS #	%	
Stoddard Solvent	8052-41-3	100	
Health	Flammability	Reactivity	Basis
1	2	0	Recommended by SPS
Exposure Limits:			Basic
			Recommended by SPS
TLV 100 ppm for 8 hour day			

SECTION 3 – PHYSICAL DATA

Boiling Point: 325 Deg F – 400 Deg F	Flash Point: 129 Deg F
Vapor Pressure: 1.2	
Specific Gravity: .77	
P.H.: 7	
Evaporation Rate: Slow Actual .2	1=Butyl Acetate

SECTION 4 – FIRE & EXPLOSION DATA

HANDLING PRECAUTIONS:

This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Keep product away from ignition sources, such as heat, sparks, pilot light, static electricity and open flames.

Flammable or explosive limits (approximate percent by volume in air)
Estimated values: Lower Flammable Limits 0.9% Upper Flammable Limits 7%

NOTE: On the drum labels, the inclusion of the phrase “water may be Ineffective” is to indicate that although water can be used to cool and protect exposed material, water may not extinguish the fire unless used under favorable conditions by experienced fire fighters trained in fighting all types of flammable liquid fires.

SECTION 5- REACTIVITY DATA

Stable
Incompatible with strong oxidizers & corrosives.
Hazardous polymerization will not occur.

SECTION 6 – HEALTH DATA

Eye contact: Flush with water until irritation subsides. If irritation persists, call physician.

Skin contact: Avoid contact on bare skin as prolonged contact will cause irritation.

Inhalation: Avoid vapor in confined areas. The stronger the odor, the faster a person will show signs of dizziness or drunkenness. Use approved breathing equipment if working in confined area.

Ingestion: Do not induce vomiting. Call a physician immediately.

SECTION 7- ENVIRONMENTAL INFORMATION

Steps to be taken in case material is released or spilled. Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth, or other suitable absorbent to spilled area. Minimize breathing vapors. Minimize skin contact. Ventilate confined areas. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas.

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, flammable vapors from absorbed material.

October 17, 2002